Customer's Response

- The response object

The response object

For each endpoint the customer object will be returned
Example:

```json
{
    "customer_id": "0fce48b7a1beff60b8ffeeda50d6bc5a",
    "first_name": "John",
    "last_name": "Doe",
    "email": "johndoe@test.es",
    "client_page": "https://smartadminadv.backend.test/checkout-client/edit?hash=b49ae24dc21c1c4c211322d73b009c54",
    "metaData": {
        "kundnummer": "00000000"
    },
    "savedCards": [
        {
            "card_id": "Iz76SvROAhZEOraU",
            "brand": "mastercard",
            "country": "GB",
            "expires": "5/2045",
            "funding": "credit",
            "last4": "4449",
            "card_holder": "Test Holder MC"
        },
        {
            "card_id": "qNpdctqqDpIsIkKu",
            "brand": "visa",
            "country": "US",
            "expires": "4/2024",
            "funding": "credit",
            "last4": "4242",
            "card_holder": "Test Holder"
        }
    ]
}
```

The customer object also returns a "Client_page", following this link the customer can change the card configuration by adding/deleting and set the default a card for a future payment.

John Doe `Test`

Card List +

---

mastercard **** 4449 🇬🇧	**Card Holder**	Delete
Expires May 2045	Test Holder MC	

---

visa **** 4242 🇺🇸	**Card Holder**	Delete
Expires Apr 2024	Test Holder	